

XUX5ANBNT16

photo-electric sensor - XUX - diffuse - Sn 2.1m
- 12..24VDC - terminals



Main

Range of product	OsiSense XU
Series name	Optimum
Specific application of photoelectric detector	Object
Sensor name	XUX
Sensor design	Compact
Material	Plastic
Detection system	Diffuse
Emission	Infrared diffuse
[Sn] nominal sensing distance	2.1 m diffuse
Wiring technique	3 wires
Type of output signal	Discrete
Discrete output function	1 NC
Discrete output type	NPN
Add on output	Without
Electrical connection	Screw-clamp terminals , 1 x 1.5 mm ² or 1 x 0.75 mm ² with adaptor
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Switching capacity in mA	≤ 100 mA , overload and short-circuit protection

Complementary

Electronic sensor type	Photo-electric sensor
Enclosure material	PBT
Lens material	PMMA
Maximum sensing distance	3 m diffuse
Output type	Solid state
Cable entry	1 entry for M16 x 1.5 cable gland , cable outer diameter: 7...10 mm
Status LED	1 LED (yellow) for output state 1 LED (green) for supply
Supply circuit type	DC
Supply voltage limits	10...36 V DC
Switching frequency	≤ 250 Hz
Voltage drop	≤ 1.5 V (closed state)
Current consumption	≤ 35 mA at no-load
Delay first up	< 15 ms
Delay response	< 2 ms
Delay recovery	< 2 ms
Setting-up	Sensitivity adjustment
Depth	30 mm
Height	92 mm
Width	77 mm
Product weight	0.2 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Product certifications	CE CSA UL
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...70 °C
Vibration resistance	7 gn , amplitude +/- 1.5 mm (f = 10...55 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn , duration 11 ms conforming to IEC 60068-2-27
IP degree of protection	IP65 double insulation conforming to IEC 60529 IP67 double insulation conforming to IEC 60529
RoHS EUR conformity date	4Q2009
RoHS EUR status	Will be compliant