



Figure similar

SIMATIC S7-400, analog input SM 431, isolated 8 AI, resolution 14 bit, U/I Resistor 8 AI, cycle time 0.416 ms

Supply voltage	
Load voltage L+	
Rated value (DC)	24 V; Only required for supplying 2-wire transmitters
Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	200 mA; for 8 connected, fully controlled 2-wire transmitters
from backplane bus 5 V DC, max.	1 000 mA
Power loss	
Power loss, typ.	4.9 W
Analog inputs	
Number of analog inputs	8
For voltage/current measurement	8
For resistance measurement	4
permissible input voltage for voltage input (destruction limit), max.	18 V; 18 V continuous, 75 V for 1 ms (mark to space ratio 1:20)
permissible input current for current input (destruction limit), max.	40 mA; Permanent
Constant measurement current for resistance-type transmitter, typ.	1.67 mA
Input ranges	
Voltage	Yes
Current	Yes
Thermocouple	No
Resistance thermometer	No
Resistance	Yes
Input ranges (rated values), voltages	
1 V to 5 V	Yes
— Input resistance (1 V to 5 V)	10 MΩ
-1 V to +1 V	Yes
— Input resistance (-1 V to +1 V)	10 MΩ
-10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	100 kΩ
Input ranges (rated values), currents	
-20 mA to +20 mA	Yes
— Input resistance (-20 mA to +20 mA)	50 Ω
4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	50 kΩ
Input ranges (rated values), resistors	
0 to 600 ohms	Yes

Cable length			
• shielded, max.		200 m	
Analog value generation for the inputs			
Integration and conversion time/resolution per channel			
• Resolution with overrange (bit including sign), max.		14 bit; 14 / 14 / 14	
• Integration time, parameterizable		Yes	
• Basic conversion time (ms)		52 µs	
• Interference voltage suppression for interference frequency f1 in Hz		none / 400 / 60 / 50 Hz	
• Time constant of the input filter		15 µs	
• Basic execution time of the module (all channels released)		0.42 ms	
Encoder			
Connection of signal encoders			
• for voltage measurement		Yes; possible	
• for current measurement as 2-wire transducer		Yes	
• for current measurement as 4-wire transducer		Yes	
• for resistance measurement with two-wire connection		Yes; Line resistances are also measured	
• for resistance measurement with three-wire connection		Yes; Line resistances are also measured	
• for resistance measurement with four-wire connection		Yes	
Errors/accuracies			
Temperature error (relative to input range), (+/-)		0.03 %/K	
Operational error limit in overall temperature range			
• Voltage, relative to input range, (+/-)		0.7 %; ±0.7 % at ±1 V; ±0.9 % at ±10 V, 1 to 5 V	
• Current, relative to input range, (+/-)		0.8 %; at ±20 mA, 4 to 20 mA	
• Resistance, relative to input range, (+/-)		1 %	
Basic error limit (operational limit at 25 °C)			
• Voltage, relative to input range, (+/-)		0.6 %; 0.6 % at ±1 V; 0.75 % at ±10 V, 1 to 5 V	
• Current, relative to input range, (+/-)		0.7 %; at ±20 mA, 4 to 20 mA	
• Resistance, relative to input range, (+/-)		0.7 %; 0 to 600 ohms	
Interrupts/diagnostics/status information			
Diagnostics function		No	
Potential separation			
Potential separation analog inputs			
• Potential separation analog inputs		Yes; internal/external	
• between the channels		No	
• between the channels and backplane bus		Yes	
• Between the channels and load voltage L+		Yes	
Isolation			
Isolation tested with		2 120 V DC between bus and analog section; 500 V DC between bus and local ground; 500 V DC between analog part and L+/M; 2 120 V DC between analog part and local ground; 2 120 V DC between L+/M and local ground	
Dimensions			
Width		25 mm	
Height		290 mm	
Depth		210 mm	
Weights			
Weight, approx.		500 g	
Classifications			
		Version	Classification
	eClass	16	27-24-22-01
	eClass	14	27-24-22-01
	eClass	12	27-24-22-01
	eClass	9.1	27-24-22-01
	eClass	9	27-24-22-01
	eClass	8	27-24-22-01
	eClass	7.1	27-24-22-01
	eClass	6	27-24-22-01

ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



[Metrological Approval](#)



General Product Approval

EMV



[China RoHS](#)

[Miscellaneous](#)

[Manufacturer Declaration](#)



For use in hazardous locations



[FM](#)



[Type Examination Certificate](#)

For use in hazardous locations

Maritime application



[NK / Nippon Kaiji Kyokai](#)

Maritime application



[CCS \(China Classification Society\)](#)

last modified:

8/7/2026