



SIMATIC S7-400, analog output SM 432, isolated 8 AO; resolution 13 bit, U/I

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from supply and load voltage L+ (without load), max.	200 mA; at rated load: max. 400 mA
from backplane bus 5 V DC, max.	150 mA
Power loss	
Power loss, typ.	9 W
Analog outputs	
Number of analog outputs	8
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	30 mA
Current output, no-load voltage, max.	19 V
Output ranges, voltage	
• 0 to 10 V	Yes
• 1 V to 5 V	Yes
• -10 V to +10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes
Connection of actuators	
• for voltage output two-wire connection	Yes; possible, without compensation of the line resistances
• for voltage output four-wire connection	Yes; possible
• for current output two-wire connection	Yes; possible
Load impedance (in rated range of output)	
• with voltage outputs, min.	1 kΩ
• with voltage outputs, capacitive load, max.	1 μF
• with current outputs, max.	500 Ω; 600 ohms if common-mode-voltage reduced to <1 V
Cable length	
• shielded, max.	200 m
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	13 bit
• Conversion time (per channel)	420 μs; 420 μs in the ranges 1 to 5 V and 4 to 20 mA; 300 μs in all ranges
Settling time	
• for resistive load	0.1 ms
• for capacitive load	3.5 ms

• for inductive load	0.5 ms																																													
Errors/accuracies																																														
Operational error limit in overall temperature range																																														
• Voltage, relative to output range, (+/-)	0.5 %; ±10 V, 0 to 10 V, 1 to 5 V																																													
• Current, relative to output range, (+/-)	1 %; ±20 mA, 4 to 20 mV																																													
Basic error limit (operational limit at 25 °C)																																														
• Voltage, relative to output range, (+/-)	0.5 %; ±10 V, 0 to 10 V, 1 to 5 V																																													
• Current, relative to output range, (+/-)	0.5 %; ±20 mA, 0 to 20 mA																																													
Interrupts/diagnostics/status information																																														
Diagnostics function	No																																													
Potential separation																																														
Potential separation analog outputs																																														
• between the channels	No																																													
• between the channels and backplane bus	Yes																																													
• Between the channels and load voltage L+	Yes																																													
Isolation																																														
Isolation tested with	2 120 V DC between bus and L+/M; 2 120 V DC between bus and analog section; 500 V DC between bus and local ground; 500 V DC between analog section and L+/M; 2 120 V DC between analog section and local ground; 2 120 V DC between L+/M and local ground																																													
Dimensions																																														
Width	25 mm																																													
Height	290 mm																																													
Depth	210 mm																																													
Weights																																														
Weight, approx.	650 g																																													
Classifications																																														
	<table><tr><th></th><th>Version</th><th>Classification</th></tr><tr><td>eClass</td><td>16</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>14</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>12</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>9.1</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>9</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>8</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>6</td><td>27-24-22-01</td></tr><tr><td>ETIM</td><td>10</td><td>EC001420</td></tr><tr><td>ETIM</td><td>9</td><td>EC001420</td></tr><tr><td>ETIM</td><td>8</td><td>EC001420</td></tr><tr><td>ETIM</td><td>7</td><td>EC001420</td></tr><tr><td>IDEA</td><td>4</td><td>3562</td></tr><tr><td>UNSPSC</td><td>15</td><td>32-15-17-05</td></tr></table>		Version	Classification	eClass	16	27-24-22-01	eClass	14	27-24-22-01	eClass	12	27-24-22-01	eClass	9.1	27-24-22-01	eClass	9	27-24-22-01	eClass	8	27-24-22-01	eClass	7.1	27-24-22-01	eClass	6	27-24-22-01	ETIM	10	EC001420	ETIM	9	EC001420	ETIM	8	EC001420	ETIM	7	EC001420	IDEA	4	3562	UNSPSC	15	32-15-17-05
	Version	Classification																																												
eClass	16	27-24-22-01																																												
eClass	14	27-24-22-01																																												
eClass	12	27-24-22-01																																												
eClass	9.1	27-24-22-01																																												
eClass	9	27-24-22-01																																												
eClass	8	27-24-22-01																																												
eClass	7.1	27-24-22-01																																												
eClass	6	27-24-22-01																																												
ETIM	10	EC001420																																												
ETIM	9	EC001420																																												
ETIM	8	EC001420																																												
ETIM	7	EC001420																																												
IDEA	4	3562																																												
UNSPSC	15	32-15-17-05																																												
Approvals / Certificates																																														
General Product Approval																																														
 EG-Konf.	Miscellaneous																																													
	 UL																																													
	Metrological Approval																																													
																																														
General Product Approval																																														
EMV																																														
 RCM	China RoHS																																													
Miscellaneous	Manufacturer Declaration																																													
 RCM	 RCM																																													

For use in hazardous locations



IECEEx



ATEX

[FM](#)



CCC



IECEEx

[Type Examination Certificate](#)

For use in hazardous locations

Maritime application



ATEX



ABS



DNV



LRS

[NK / Nippon Kaiji Kyokai](#)

Maritime application



PRS



RINA



RMRS

[CCS \(China Classification Society\)](#)

last modified:

8/7/2026