

PNOZ s50 C

751500



Safety relay (standalone) Control/monitoring of inductive actuators, such as brakes and valves UB 24/48 V DC, max. 3.5/1.75 A continuous current/ max. 6.5/3.25 A output current in accordance with PL e and SIL 3 Display operation push&turn Plug-in spring-loaded terminals.

Dane

Zezwolenia:	CE;cULus Listed;TÜV
Możliwości zastosowania:	Sicheres PWM-Schaltgerät
Normy:	EN 60204-1;EN 62061;EN ISO 13849-1
Typ zacisku:	Zacisk sprężynowy
Napięcie zasilania (V):	24,0
Rodzaj napięcia zasilania 2:	DC
Szerokość:	45.0 mm
Wymiar wysokości:	100.0 mm
Wymiar głębokości:	120.0 mm
Ciężar brutto:	275 g
Ciężar netto:	255 g
Temperatura otoczenia:	0 - 55 °C

Akcesoria opcjonalne



751008

PNOZ s Set1spring loaded terminals 45mm



779200

PNOZmulti Chipcard Set 10 piece



779201

PNOZmulti Chipcard 1 piece



779211

Chipcard 1 piece 32kB



779212

PNOZmulti Chipcard Set 10 pieces 32kB



779230

PNOZ Chip Card Reader



779240

PNOZmulti Chipcard Holder (Sparepart)



779250

PNOZmulti Seal 12 pieces



750030

PNOZsigma Chip Card-manager set



750031

SmartCardCommander with SIM-card-adapter