

XCMD4102L5EX

limit switch XCM-D - roller plunger - 2 x (1 NC + 1 NO) - ATEX

Main

Range of product	Osiswitch ATEX D
Series name	Universal
Product or component type	Limit switch
Device short name	XCMD
Sensor design	Miniature
Body type	Fixed
Head type	Plunger head
Material	Metal
Fixing mode	By the body
Type of operator	Spring return roller plunger steel
Switch actuation	By 30° cam
Type of approach	Lateral approach 2 directions
Electrical connection	Fixed cable
Number of poles	4
Contacts type and composition	2 x (1 NC + 1 NO)
Contacts insulation form	Zb
Contacts operation	Snap action
Number of steps	1
Positive opening	With
Minimum force for tripping	7 N
Maximum actuation speed	0.5 m/s
IP degree of protection	IP66 IEC 60529 IP67 IEC 60529

Complementary

Body material	Zamak
Head material	Zamak
Movement of operating head	Linear
Cable length	5 m
Cable composition	9 x 0.34 mm ²
Wire insulation material	PvR
Positive opening minimum force	35 N
Minimum actuation speed	0.01 m/min
Contact code designation	C300 AC-15 240 V 0.75 A IEC 60947-5-1 appendix A C300 AC-15 240 V 0.75 A EN 60947-5-1 R300 DC-13 250 V 0.1 A EN 60947-5-1 R300 DC-13 250 V 0.1 A IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	3 A AC
[Ui] rated insulation voltage	300 V UL 508 300 V CSA C22-2 No 14 400 V 3 IEC 60947-1
Resistance across terminals	≤ 25 mOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	4 kV IEC 60947-1 4 kV IEC 60664
Short circuit protection	6 A cartridge fuse gG

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Electrical durability	5000000 cycles DC-13 inductive 120 V 1 W ≤ 3600 cyc/h 0.5 DC IEC 60947-5-1 appendix C 5000000 cycles DC-13 inductive 48 V 2 W ≤ 3600 cyc/h 0.5 DC IEC 60947-5-1 appendix C 5000000 cycles DC-13 inductive 24 V 3 W ≤ 3600 cyc/h 0.5 DC IEC 60947-5-1 appendix C
Mechanical durability	10000000 cycles
Marking	II2 D-Ex tD A21 IP66/67 T85°C
Width	30 mm
Height	50 mm
Depth	16 mm

Environment

Shock resistance	25 gn 18 ms IEC 60068-2-27
Vibration resistance	5 gn 10...500 Hz IEC 60068-2-6
Class of protection against electric shock	Class I IEC 61140 Class I NF C 20-030
Ambient air temperature for operation	-20...60 °C
Protective treatment	TC
Dust zone	Zone 21 - 22
Product certifications	INERIS 04ATEX0014X
Standards	Directive ATEX 94/9/EC EN 50014 EN 50281-1-1 IEC 61241-0 IEC 61241-1
RoHS EUR conformity date	3Q2009
RoHS EUR status	Will be compliant