

XY2CH13470

Emergency stop trip wire switch with tensioner
- w/o pilot light



Main

Range of product	Preventa XY2
Product or component type	Latching emergency stop trip wire switch
Device short name	XY2CH
Local signalling	Without pilot light
Number of cables	1
Trigger cable maximum length	15 m
Housing colour	Grey RAL 7032
Reset	By key-release pushbutton
Contacts type and composition	2 NC
Trigger cable anchor point	RH or LH side
Connections - terminals	Screw clamp terminal 1 x 0.5...2 x 1.5 mm ²

Complementary

Key number	421
Contacts operation	Slow-break
Tightening torque	0.8...1.2 N.m
Cable entry	3 tapped entries for Pg 13.5 cable gland
Mechanical durability	10000 cycles
Distance between cable supports	5 m
[Ie] rated operational current	0.27 A at 250 V DC-13 , Q600 conforming to EN/IEC 60947-5-1 appendix A 3 A at 240 V AC-15 , A600 conforming to EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	300 V conforming to UL 508 300 V conforming to CSA C22-2 No 14 400 V , degree of pollution: 3 conforming to EN/IEC 60947-1
[Uimp] rated impulse withstand voltage	4 kV
Positive opening	With conforming to EN/IEC 60947-5-1 section 3
Resistance across terminals	≤ 25 mOhm conforming to EN/IEC 60255-7 category 3 ≤ 25 mOhm conforming to NF C 93-050 method A
Short circuit protection	10 A cartridge fuse , gG conforming to EN/IEC 60269
Height	68 mm
Width	201 mm
Depth	95 mm
Product weight	0.91 kg

Environment

Standards	EN/IEC 60947-5-1 EN/ISO 13850 UL 508
Product certifications	CCC CSA UL
Protective treatment	TC
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Vibration resistance	10 gn (f = 10...150 Hz) conforming to EN/IEC 60068-2-6

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the company mentioned herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Shock resistance	50 gn (11 ms) conforming to EN/IEC 60068-2-27
Class of protection against electric shock	Class I conforming to NF C 20-030 Class I conforming to EN/IEC 61140
IP degree of protection	IP65
RoHS EUR conformity date	4Q2009
RoHS EUR status	Will be compliant