



## MATERIAL FACT SHEET

### 587786 FR-E840-0230-4-60

#### General Data

|                     |                                     |
|---------------------|-------------------------------------|
| Product Hierarchy   | IAK24802                            |
|                     | INVERTER                            |
|                     | FR-E840                             |
| Ext. Material Group | 10 STANDARD ITEM                    |
| ABC Indicator       | B (Limited Availability from Stock) |

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IA/EUR/en/p/000000000000587786](https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000587786)

#### FA-Inverter: Inverter

|                               |                                |
|-------------------------------|--------------------------------|
| Series                        | FR-E800 SERIES                 |
| Type                          | FR-E800 RS485 INVERTER         |
| Minimum Rated Voltage (V)     | 380                            |
| Min. Permissible Voltage (V)  | 323                            |
| Maximum Rated Voltage (V)     | 480                            |
| Max. Permissible Voltage (V)  | 528                            |
| Current Type                  | AC                             |
| Phases                        | 3                              |
| Rated Output Current LD (A)   | 35                             |
| Rated Output Current ND (A)   | 23                             |
| Rated Motor Capacity LD (kW)  | 15                             |
| Rated Motor Capacity ND (kW)  | 11                             |
| Frequency Range (Hz)          | 0,2–590                        |
| Control Method                | MAGNETIC FLUX VECTOR CONTROL   |
| Control Method (2)            | PM SENSORLESS VECTOR CONTROL   |
| Control Method (3)            | REAL SENSORLESS VECTOR CONTROL |
| Control Method (4)            | V/F CONTROL                    |
| Motor Type                    | INDUCTION MOTOR, PM MOTOR      |
| Brake Chopper ED (%)          | 100                            |
| Integrated EMC Filter         | NO                             |
| Safe Torque Off (STO)         | YES                            |
| Regenerative (4Q)             | NO                             |
| Integrated DC Choke           | NO                             |
| Display                       | BUILT-IN                       |
| Display Type                  | 4 DIGITS LED                   |
| PLC Function                  | YES                            |
| Program Memory                | 2K                             |
| Program Memory Unit           | STEPS                          |
| Integrated Digital Inputs     | 7                              |
| Digital Outputs (Transistor)  | 2                              |
| Digital Outputs (Relay)       | 1                              |
| Integrated Analogue Inputs    | 2                              |
| Integrated Analogue Outputs   | 1                              |
| IO Type of Terminal Block     | SPRING CLAMP                   |
| Expandable                    | YES                            |
| RS-485                        | 1                              |
| USB                           | 1 (MINI B)                     |
| Ethernet Port                 | NO                             |
| Built-In Network              | MODBUS-RTU                     |
| Leakage Current (mA)          | 1,2                            |
| Power Loss LD (W)             | 410                            |
| Power Loss ND (W)             | 239                            |
| Standby Power Consumption (W) | -                              |
| Protection Class              | IP20                           |

#### Product Dimensions & Weight

|             |     |
|-------------|-----|
| Width (mm)  | 220 |
| Height (mm) | 260 |

|             |     |
|-------------|-----|
| Depth (mm)  | 190 |
| Weight (kg) | 4,8 |

### Logistic Dimensions & Gross Weight

|                   |        |
|-------------------|--------|
| Length (cm)       | 31,0   |
| Width (cm)        | 37,5   |
| Height (cm)       | 29,5   |
| Gross Weight (kg) | 6,379  |
| Volume (cdm)      | 34,294 |

### Stock Data

|                              |    |
|------------------------------|----|
| Planned Delivery Time (Days) | 79 |
|------------------------------|----|

### Life Cycle

|             |                           |
|-------------|---------------------------|
| Sales Start | 12.01.2021                |
| Predecessor | 240987 / FR-E740-230SC-E6 |

### Additional Product Information

|                  |    |
|------------------|----|
| Battery included | NO |
|------------------|----|

### Export Data

|                                          |            |
|------------------------------------------|------------|
| Commodity Code                           | 85044095   |
| Legal Control (Dual Use List)            | Not Listed |
| Country of Origin                        | China (CN) |
| Preference Status (Supplier Declaration) | Non EU     |

### Environmental

|                                |                            |
|--------------------------------|----------------------------|
| REACH Limit Exceeded           | YES                        |
| REACH Substance CAS Number     | <a href="#">540-97-6</a>   |
| REACH Substance CAS Number (2) | <a href="#">541-02-6</a>   |
| REACH Substance CAS Number (3) | <a href="#">71868-10-5</a> |
| REACH Substance CAS Number (4) | <a href="#">7439-92-1</a>  |
| REACH Substance CAS Number (5) | <a href="#">556-67-2</a>   |
| Dangerous Goods Class          | NO                         |
| Dangerous Goods Identifier     | NO                         |
| RoHS Compliance                | COMPLIANT                  |
| WEEE                           | B2B                        |

### Conformity

|        |           |
|--------|-----------|
| CE     | COMPLIANT |
| UL/cUL | COMPLIANT |
| EAC    | COMPLIANT |
| UKCA   | COMPLIANT |

### Documentation & Media Data

|                                |                                                                                                                                                                                                                                                                                                       |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Manual URL Indicator           | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=FR-E840-0230-4-60&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=FR-E840-0230-4-60&amp;doc-lang=en</a> |
| Certificates URL Indicator     | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=FR-E840-0230-4-60&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=FR-E840-0230-4-60&amp;doc-lang=en</a> |
| CAD URL Indicator              | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=FR-E840-0230-4-60&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=FR-E840-0230-4-60&amp;doc-lang=en</a> |
| Network configuration file URL | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blte8cf990c7c524b4e&amp;q=FR-E840-0230-4-60&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blte8cf990c7c524b4e&amp;q=FR-E840-0230-4-60&amp;doc-lang=en</a> |

### Product Packaging

|                   |      |
|-------------------|------|
| Cardboard (g)     | 0,0  |
| Other paper (g)   | 0    |
| Aluminum (g)      | 0    |
| Steel (g)         | 0    |
| Styrofoam (g)     | 91,4 |
| Other plastic (g) | 6,8  |
| Wood (g)          | 0    |
| Glass (g)         | 0    |
| Others (g)        | 0    |

### Spare parts

| Material               | Description               | Quantity | Unit |
|------------------------|---------------------------|----------|------|
| <a href="#">600706</a> | FR-E820/E840/E860 PCB CPU | 1        | PC   |
| <a href="#">611134</a> | FR-E840-4(5)-60 PCB TA    | 1        | PC   |

| Material               | Description                     | Quantity | Unit |
|------------------------|---------------------------------|----------|------|
| <a href="#">611164</a> | FR-E820-0240-0330 FAN           | 2        | PC   |
| <a href="#">611138</a> | FR-E800 parameter unit          | 1        | PC   |
| <a href="#">591470</a> | FR-A870 CABLE ALL BKO-CA1972H01 | 1        | PC   |

### Compatible products

| Material               | Description / Price List Text / Classification                                                                                                                     |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">70727</a>  | FR-A5 CBL 1<br>Cable for connecting Inverter and Programming panel; 1m<br>Class 100100405: FA-Inverter: Cable                                                      |
| <a href="#">70728</a>  | FR-A5 CBL 3<br>Cable for connecting Inverter and Programming panel; 3m<br>Class 100100405: FA-Inverter: Cable                                                      |
| <a href="#">70729</a>  | FR-A5 CBL 5<br>Cable for connecting Inverter and Programming panel; 5m<br>Class 100100405: FA-Inverter: Cable                                                      |
| <a href="#">130832</a> | FR-UDA02<br>DIN-Rail Adaptor for FR-D720S-1,5k; FR-D740-0,4k-3,7k<br>Class 100100403: FA-Inverter: External Option                                                 |
| <a href="#">166134</a> | FR-PU07<br>Programming panel with LCD-Display for all units of FR-700 series<br>Class 100100403: FA-Inverter: External Option                                      |
| <a href="#">167612</a> | FR-RJ45-HUB10<br>Distribution Module for RJ45; 10 way<br>Class 100100403: FA-Inverter: External Option                                                             |
| <a href="#">167613</a> | FR-RJ45-HUB4<br>Distribution Module for RJ45; 4 way<br>Class 100100403: FA-Inverter: External Option                                                               |
| <a href="#">167614</a> | FR-RJ45-TR<br>Terminal Resistor Plug RJ45<br>Class 100100403: FA-Inverter: External Option                                                                         |
| <a href="#">202427</a> | FR-BU2-H15K<br>Brake Unit without Brake Resistor for all Inverters with DC-Bus Terminals; 400V<br>Class 100100407: FA-Inverter: Brake Option                       |
| <a href="#">209052</a> | FR-PU07BB-L<br>Programming Panel with Copy Function; batterypowered; all FR-700 units; w/o bat.<br>Class 100100403: FA-Inverter: External Option                   |
| <a href="#">209738</a> | FFR-SI-25A-SS1<br>Sinusfilter for 200/230/400V Inverters;max. 25A;FT=4-16kHz;(W*H*D) 210*260*125mm<br>Class 100100404: FA-Inverter: Filter                         |
| <a href="#">209756</a> | FFR-DT-25A-SS1<br>du/dt Filter for 400V Inverters; max. 25A; FT=2-16kHz; (W*H*D) 125*140*80mm<br>Class 100100404: FA-Inverter: Filter                              |
| <a href="#">214795</a> | FR-PA07<br>Simple Parameter Unit for mounting on enclosure surface; for all FR-E700<br>Class 100100403: FA-Inverter: External Option                               |
| <a href="#">221540</a> | USB-CAB-5M<br>USB 2.0 connection cabel, plug USB A to plug USB B (mini), 5m<br>Class 100100303: FA-HMI: Cable                                                      |
| <a href="#">274525</a> | FR-LU08<br>Clear text LCD Parameter unit for all units of 800 Series<br>Class 100100403: FA-Inverter: External Option                                              |
| <a href="#">275503</a> | FR Configurator-M+FR-Configurator2<br>FR-Configurator for 700 series; multi I + FR-Configurator2 for 800 series<br>Class 100101203: FA-Software: Software Inverter |
| <a href="#">296613</a> | FR-LU08-01<br>Clear text LCD Parameter unit for all units of 800 Series (IP55)<br>Class 100100403: FA-Inverter: External Option                                    |
| <a href="#">506377</a> | FR-A8AX-60 E-KIT<br>16-Bit-Digital-Input; BCD/Binary-Code; 24V DC; 5mA; Coated; E-KIT for FR-E800<br>Class 100100402: FA-Inverter: Internal Option                 |
| <a href="#">506378</a> | FR-A8AY-60 E-KIT<br>Digital-/Analog Output; Output load: 24V DC; 0,1A; Coated; E-KIT for FR-E800<br>Class 100100402: FA-Inverter: Internal Option                  |
| <a href="#">506379</a> | FR-A8AR-60 E-KIT<br>Relay output; 3 additional output relays; Coated; E-KIT for FR-E800<br>Class 100100402: FA-Inverter: Internal Option                           |
| <a href="#">506380</a> | FR-A8NP-60 E-KIT<br>Profibus Network connection; Coated; E-KIT for FR-E800<br>Class 100100402: FA-Inverter: Internal Option                                        |

| Material               | Description / Price List Text / Classification                                                                               |
|------------------------|------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">506381</a> | FR-A8ND-60 E-KIT<br>DeviceNet Network connection; Coated; E-KIT for FR-E800<br>Class 100100402: FA-Inverter: Internal Option |
| <a href="#">506412</a> | FR-A8NC-60 E-KIT<br>CC-Link Network connection; Coated; E-KIT for FR-E800<br>Class 100100402: FA-Inverter: Internal Option   |
| <a href="#">573101</a> | FR-A8AP-60 E-KIT<br>Incremental Encoder Feedback; E-KIT for FR-E800; Coated<br>Class 100100402: FA-Inverter: Internal Option |
| <a href="#">593978</a> | FFR-E-MSH-300-55A-SF1<br>Radio Noise Filter for FR-E840-230/300; C1 20m, C2 100m<br>Class 100100404: FA-Inverter: Filter     |