



Main

Enclosure type	Distribution enclosure
Range of product	Pragma
Device short name	Pragma
Accessories included with enclosure	2 terminal blocks Blanking plate strip Identification label Marking kit

Complementary

Enclosure mounting	Flush
[In] rated current	125 A
Type of front cover	Customizable Transparent
Number of horizontal rows	3
Number of 18 mm modules per row	18
Total number of 18 mm modules	54
Type of rail	DIN
Cable entry	Cable or tube Removable plates Side pre-cutouts
Number of terminal blocks	Earth: 1 Quick with 26 outgoing Neutral: 1 Quick with 24 outgoing
Distribution block outgoing	1 x 25 mm ² for earth 1 x 50 mm ² for neutral 1 x 50 mm ² for earth 3 x 25 mm ² for neutral 20 x 6 mm ² for neutral 24 x 6 mm ² for earth
Power dissipation in W	68 W
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic
Width	486 mm
Height	630 mm wall 660 mm outside
Depth	43 mm outside 86 mm wall
Colour	Door : crystal Enclosure : titanium white Front face : metal grey

Environment

Standards	EN 60439-3 EN 60695-2-11 IEC 60439-3 IEC 60529 IEC 60695-2-11 IEC 60947-7-1 IEC 62262
Fire resistance	Back part: 650 °C conforming to IEC 60695-2-1 Door: 650 °C conforming to IEC 60695-2-1 Front face: 650 °C conforming to IEC 60695-2-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK09 conforming to IEC 62262
Electrical shock protection class	Class II
Ambient air temperature for operation	-25...60 °C
RoHS EUR conformity date	0810
RoHS EUR status	Compliant