



Main

Enclosure type	Distribution enclosure
Range of product	Pragma
Device short name	Pragma
Accessories included with enclosure	2 terminal blocks Blanking plate strip Identification label Marking kit

Complementary

Enclosure mounting	Flush
[In] rated current	90 A
Type of front cover	Opaque
Number of horizontal rows	1
Number of 18 mm modules per row	18
Total number of 18 mm modules	18
Type of rail	DIN
Cable entry	Cable or tube Removable plates Side pre-cutouts
Number of terminal blocks	Earth: 1 Quick with 17 outgoing Neutral: 1 Quick with 15 outgoing
Distribution block outgoing	1 x 25 mm ² for earth 3 x 25 mm ² for neutral 12 x 6 mm ² for neutral 16 x 6 mm ² for earth
[Ui] rated insulation voltage	800 V
Power dissipation in W	45 W
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic
Width	486 mm
Height	330 mm wall 360 mm outside
Depth	43 mm outside 86 mm wall
Colour	Door : titanium white Enclosure : titanium white Front face : metal grey

Environment

Standards	EN 60439-3 EN 60695-2-11 IEC 60439-3 IEC 60529 IEC 60695-2-11 IEC 60947-7-1 IEC 62262
Fire resistance	Back part: 650 °C conforming to IEC 60695-2-1 Door: 650 °C conforming to IEC 60695-2-1 Front face: 650 °C conforming to IEC 60695-2-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK09 conforming to IEC 62262
Electrical shock protection class	Class II
Ambient air temperature for operation	-25...60 °C
RoHS EUR conformity date	0810
RoHS EUR status	Compliant