



Main

Range of product	Harmony XALD
Product or component type	Empty control station
Device short name	XALD
Product destination	For XB5 Ø 22 mm control and signalling units
Number of cut-out	4 cut-outs
Colour of base of enclosure	Light grey RAL 7035
Colour of cover	Dark grey RAL 7016
Material	Polycarbonate
IP degree of protection	IP65 conforming to IEC 60529

Complementary

Assembly style	For customer assembly
Cable entry	2 knock-outs for Pg 13 cable gland and ISO M20 , clamping capacity: ≤ 12 mm 2 knock-outs for cable entry , clamping capacity: ≤ 14 mm
Resistance to high pressure washer	7000000 Pa at 55 °C , distance: 0.1 m

Environment

Protective treatment	TH
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-25...70 °C
Class of protection against electric shock	Class II conforming to IEC 60536
NEMA degree of protection	NEMA 13 NEMA 4X
IK degree of protection	IK03 conforming to EN 50102
Standards	CSA C22-2 No 14 EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 UL 508
Product certifications	CSA UL
RoHS EUR conformity date	0903
RoHS EUR status	Compliant