



Main

Range of product	Harmony XVD Optimum
Product or component type	Complete miniature beacon
Beacon/Indicator bk unit type	Base unit with direct fixing mode Illuminated unit
Signalling type	Flashing
Mounting diameter	45 mm
Component name	XVDLS
Material	Glass reinforced polyamide (base unit) Polycarbonate (illuminated unit)
Light source	Red integral flash discharge tube
Bulb type	Flash discharge tube
[Us] rated supply voltage	230 V AC

Complementary


Connections - terminals	Screw clamp terminals, connection capacity: ≤ 1 x 1.5 mm ² with cable end
Cable entry	1 tapped entry for Pg 7
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1
Current consumption	< 25 mA AC
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-1
Flash energy	1 J
CAD overall width	45 mm
CAD overall height	104 mm
CAD overall depth	45 mm
Terminals description ISO n°1	(COM-1)PW (GND)GROUND
Product weight	0.085 kg

Environment

Product certifications	CSA UL
Standards	EN/IEC 60947-5-1
Protective treatment	TC
Ambient air temperature for storage	-40...70 °C
Class of protection against electric shock	Class II conforming to IEC 60536
IP degree of protection	IP40
RoHS EUR status	Compliant
RoHS EUR conformity date	0907

Illuminated Beacon

Dimensions



Illuminated Beacon

Panel Cut-out for Direct Fixing

