



Fotoprzełączniki W2 Flat, Fotoprzełącznik odbiciowy, energetyczny

WT2F-P150



Nazwa modelu > **WT2F-P150**

Numer części > **6030580**



Produkt może różnić się od ilustracji

At a glance

- V-optic sensor with fixed sensing ranges of 9 mm or 18 mm for detecting transparent and glossy objects
- Energetic proximity sensor with fixed sensing ranges of 34 or 115 mm
- Rugged housing with metal sleeves for 2 mm fixing screws included with delivery
- 0.5 ms response time
- IP 67 enclosure rating
- Red light

Your benefits

- Variants with V-optics reliably detect transparent and glossy objects, resulting in a low-cost application solution - even for demanding applications
- Smart, optimal design fits into small spaces, providing increased application flexibility
- Sensors with four fixed sensing ranges provides a wide range of application options
- Quick and easy installation since sensors can be mounted directly to the machine



Cechy

Wymiary (Szer. x Wys. x Głęb.):	14 mm x 19,5 mm x 3,5 mm
Maks. strefa działania:	2 mm ... 34 mm
Sensing range:	2 mm ... 34 mm
Housing desig (light emission):	Prostopadłościenna, Flat
Nadajnik światła:	LED ¹⁾
Rodzaj światła:	widzialne światło czerwone
Długość fali:	660 nm
Zasada działania czujnika/Sposób detekcji:	Fotoprzeźnik odbiciowy, energetyczny


¹⁾ Average service life of 100,000 h at T_A = +25 °C

Mechanika/elektronika

Rodzaj zabezpieczenia:	IP 67
Napięcie zasilania:	12 V DC ... 24 V DC ¹⁾
Tętnienia resztkowe:	$\leq 5 \text{ Vss}$ ²⁾
Wyjście przełączające:	PNP, light switching
Output current I _{max} :	50
Czas reakcji:	$\leq 0,5 \text{ ms}$ ³⁾
Switching frequency:	1.000 ⁴⁾
Sposób przyłączenia:	Cable, 3-wire, 2 m ⁵⁾
Cable material:	PVC
Cable diameter:	2,4 mm
Układ zabezpieczenia:::	A C ⁶⁾ 7) 8) D
Ciężar:	20 g
Tworzywo, obudowa:	PC
Tworzywo, układ optyczny:	PC
Ambient temperature, operation:	-20 °C ... 55 °C
Ambient temperature, storage:	-40 °C ... 75 °C
Filtr polaryzacyjny:	-
Napięcie sygnału NPN HIGH/LOW:	ca. $U_v / < 1,8 \text{ V}$
Ognisko nastawne:	-
Napięcie sygnału PNP HIGH/LOW:	approx. $V_S - 1.8 \text{ V} / 0 \text{ V}$
Zabezpieczenie przed zmianą biegunowości:	✓
Zabezpieczenie przed zwarciami:	✓


¹⁾ $\pm 10 \%$ ²⁾ May not exceed or fall short of V_S ³⁾ Signal transit time with resistive load ⁴⁾ With light/dark ratio 1:1 ⁵⁾ Do not bend below 0 °C ⁶⁾ $A = V_S$ connections
reverse-polarity protected ⁷⁾ C = interference suppression ⁸⁾ D = outputs overcurrent and short-circuit protected

Dimensional drawing




- [1] Mounting holes, $\varnothing 2.1 \text{ mm}$
- [2] Optical axis, sender
- [3] Optical axis, receiver
- [4] LED indicator orange: switching output active
- [5] LED indicator green: strength indicator
- [6] Connection


Connection diagram




Connection type



Characteristic curve



Sensing range diagram



1	Scanning distance on black, 6 % remission
2	Scanning distance on grey, 18 % remission
3	Scanning distance on white, 90 % remission

Australia

Phone +61 3 9497 4100
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

Ceská Republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +852-2763 6966
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail kundenservice@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-999-0590
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederlands

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7 495 775 05 30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail admin@sicksgp.com.sg

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82-2 786 6321/4
E-Mail info@sickkorea.net

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886 2 2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 216 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com