



Photoelectric sensors W11-2, Fotoprzełącznik odbiciowy, energetyczny

WTE11-2P2432



Nazwa modelu > **WTE11-2P2432**

Numer części > **1041381**



At a glance

- Energetic proximity sensor
- Rugged housing for industrial use
- PinPoint LED technology with a highly visible light spot
- Space-saving plastic housing in chemically, thermally or mechanically resistant designs
- Dovetail mounting - standard mounting holes and oblong holes
- Highly visible 360° status LEDs
- Simple sensing distance adjustment via teach-in pushbutton
- Operating distance up to 1,000 mm

Your benefits

- Reliable detection of objects ranging from light to dark thanks to superior chip technology
- PinPoint LED technology provides a bright, small and precise light spot that enables quick and easy sensor alignment
- Precise switching characteristics ensure high performance even in changing application conditions
- Rugged housing design withstands harsh environments, reducing downtime and maintenance effort
- Highly visible 360° status LEDs provide quick and easy setup without additional personnel or costly training
- Easy installation using SICK accessories



Cechy

Wymiary (Szer. x Wys. x Głęb.):	15,6 mm x 48,5 mm x 42 mm
Maks. strefa działania:	40 mm ... 1.000 mm ¹⁾
Sensing range:	40 mm ... 600 mm
Housing desig (light emission):	Prostopadłościenna
Nadajnik światła:	LED ²⁾
Rodzaj światła:	widzialne światło czerwone
Długość fali:	633 nm
Nastawienie czułości:	Teach
Teach-in:	single teach-in button
Zasada działania czujnika/Sposób detekcji:	Fotoprzełącznik odbiciowy, energetyczny
Light spot (distance):	90 mm (600 mm)


¹⁾ Obiekt odbijający 90% światła (standardowy biały zgodnie z norma DIN 5033) ²⁾ Average service life 100,000 h at Ta = +25 °C

Mechanika/elektronika

Rodzaj zabezpieczenia:	IP 66 IP 67
Napięcie zasilania:	10 V DC ... 30 V DC ¹⁾
Tętnienia resztkowe:	≤ 5 Vss ²⁾
Pobór prądu:	≤ 30 mA ³⁾
Wyjście przełączające:	PNP, przełączanie jasno/ciemno, wybierane, Komplementarne
Output current I _{max} :	100 mA
Czas reakcji:	≤ 2,5 ms ⁴⁾
Switching frequency:	200 Hz ⁵⁾
Sposób przyłączenia:	Connector M12, 4-pin
Klasa ochronności:	II
Układ zabezpieczenia:::	A C ⁶⁾ 7) 8) D
Ciężar:	120 g
Tworzywo, obudowa:	ABS
Tworzywo, układ optyczny:	PMMA
Ambient temperature, operation:	-30 °C ... 60 °C
Ambient temperature, storage:	-40 °C ... 75 °C
Napięcie sygnału PNP HIGH/LOW:	U _v - 2,5 V/ca. 0 V
UL File-No.:	UL No. NRKH.E181493 & cUL No. NRKH7.E181493

¹⁾ Limit values, operation in short-circuit protected network max. 8 A ²⁾ May not exceed or fall short of V_S ³⁾ Without load ⁴⁾ Signal transit time with resistive load ⁵⁾ With light/dark ratio 1:1 ⁶⁾ A = V_S connections reverse-polarity protected ⁷⁾ C = interference suppression ⁸⁾ D = outputs overcurrent and short-circuit protected


Dimensional drawing




Einstell-Möglichkeiten




Connection diagram




Connection type



Characteristic curve



Sensing range diagram



1	Scanning distance on black, 6 % remission
2	Scanning distance on grey, 18 % remission
3	Scanning distance on white, 90 % remission

Australia

Phone +61 3 9497 4100
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

Ceská Republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +852-2763 6966
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail kundenservice@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-999-0590
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederlands

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7 495 775 05 30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail admin@sicksgp.com.sg

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82-2 786 6321/4
E-Mail info@sickkorea.net

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886 2 2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 216 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com