



Fotoprzełączniki W4S-3 Inox, Fotoprzełącznik odbiciowy, Tłumienie przedpola

WTF4S-3P2262V



Nazwa modelu > **WTF4S-3P2262V**

Numer części > **1046410**



At a glance

- WashDown rated for fluid tightness (IP 66, IP 67, IP 68 and IP 69K) and Ecolab certified
- Tough stainless steel housing (316L/1.4404)
- Resistant to a variety of common cleaning and disinfection agents
- Modern electrical connection available - M12 connector with pin casting
- Best extraneous light suppression in its class with OES3 technology and two emitter LED's
- Teach-in via stainless steel pushbutton with a metal membrane
- PinPoint LED technology provides a highly visible laser-like light spot

Your benefits

- Long service life in harsh conditions ensures less downtime and fewer replacement costs
- OES3 technology and special optical design ensures reliable detection of objects at an extended range which ensures less machine downtime caused by faulty switching
- Economical and efficient machine integration without a reflector, all the sensor needs is a fixed background for calibration
- Quick and easy alignment due to highly visible PinPoint emitter LED
- Easy adjustment via stainless steel metal membrane teach button



Cechy

Wymiary (Szer. x Wys. x Głęb.):	15,25 mm x 44,9 mm x 22,2 mm
Maks. strefa działania:	20 mm ... 200 mm ¹⁾
Housing desig (light emission):	Prostopadłościenna, Slim
Nadajnik światła:	Pin Point LED ²⁾
Rodzaj światła:	widzialne światło czerwone
Długość fali:	650 nm
Nastawienie czułości:	Teach
Teach-in:	single teach-in button
Zasada działania czujnika/Sposób detekcji:	Fotoprzełącznik odbiciowy, Tłumienie przedpola
Light spot (distance):	Ø 6,5 mm (150 mm)

¹⁾ Obiekt odbijający 90% światła (standardowy biały zgodnie z normą DIN 5033) ²⁾ Average service life 100,000 h at Ta = +25 °C

Mechanika/elektronika

IP 66
IP 67
IP 68
IP 69K 1)

10 V DC ... 30 V DC ²⁾

 $\leq 5 \text{ V/}\epsilon\epsilon$ 3) $\leq 30 \text{ mA}^{4)}$

PNP, przełączanie jasno/ciemno, wybierane

 $\leq 100 \text{ mA}$ $< 0.5 \text{ ms}^{5)}$

1.000 Hz⁶⁾

Connector M8, 4-pin

III

A
B 7) 8) 9)
C

40 g

Edelstahl 316L

-35 °C ... 70 °C 10)
-35 °C ... 60 °C

-35 °C ... 75 °C

UL No. NRKH.E181493 & cUL No. NRKH7.E181493


1) Only in case of correctly mounted IP 69K connecting cable 2) Limit values, reverse-polarity protected, operation in short-circuit protected network, max. 8 A 3) May not exceed or fall short of V_S 4) Without load 5) Signal transit time with resistive load 6) With light/dark ratio 1:1 7) A = V_S connections reverse-polarity protected 8) B = inputs and output reverse-polarity protected 9) C = interference suppression 10) At UV ≤ 24 V and IA < 30 mA

[illegible]


- [1] Center of optical axis, receiver
- [2] Center of optical axis, sender
- [3] Threaded mounting hole M3
- [4] Status indicator LED,
yellow: Status of received light beam
- [5] Status indicator LED green: power on
- [6] Teach-in button

All dimensions in mm (inch)

Connection diagram



Connection type



Australia

Phone +61 3 9497 4100
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

Ceská Republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +852-2763 6966
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail kundenservice@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-999-0590
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederlands

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7 495 775 05 30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail admin@sicksgp.com.sg

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82-2 786 6321/4
E-Mail info@sickkorea.net

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886 2 2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 216 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com