


XCRZ15

contact block XCRZ - 2X(1NO+NC) - slow
break, break before make



Main

Range of product	OsiSense XC
Series name	Special format
Product or component type	Limit switch contact block with mounting plate
Device short name	XCRZ
Product compatibility	XCRA XCRB XCRE XCRF
Electrical connection	Screw-clamp terminals , 1 x 0.5...2 x 2.5 mm ²
Number of poles	4
Contacts type and composition	2 x (1 NC + 1 NO)
Contacts operation	Slow-break, break before make
Contacts material	Silver plated contacts
Positive opening	With (only NO)

Complementary

Contacts insulation form	Zb
Minimum actuation speed	6 m/min
Contact code designation	A300; AC-15(U _e = 240 V, I _e = 3 A) EN/IEC 60947-5-1 appendix A Q300; DC-13(U _e = 250 V, I _e = 0.27 A) EN/IEC 60947-5-1 appendix A
Resistance across terminals	< 25 mOhm IEC 60255-7 category 3
[Ui] rated insulation voltage	300 V CSA C22-2 No 14 300 V UL 508 500 V 3 IEC 60947-1 500 V NF C 20-040 group C 500 V VDE 0110
[Uimp] rated impulse withstand voltage	6 kV IEC 60664 6 kV IEC 60947-1
Short circuit protection	10 A cartridge fuse gG
Electrical durability	5000000 cycles DC-13,120 V 7 W,< 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles DC-13,24 V 13 W,< 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles DC-13,48 V 9 W,< 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.