

Fotoprzełączniki W12G, Fotoprzełącznik refleksyjny, autocollimation

WL12G-302431S47



Nazwa modelu > **WL12G-3O2431S47**

Numer części > **1044114**



Produkt może różnić się od ilustracji

At a glance

- Reliable detection of transparent objects
- Optional Continuous Threshold Adaption (CTA)
- Sensing range is adjustable via potentiometer or teach-in pushbutton
- Rugged housing for industrial use
- Highly visible red light spot for versatile detection of objects
- Quality monitoring thanks to IO-Link
- Key lock function, remote teach
- Diagnostics messages (contamination and short-circuit)

Your benefits

Reliable detection of transparent objects, including PET bottles and transparent film
PinPoint LED technology provides a bright, small and precise light spot that enables quick and easy sensor alignment

Precise switching characteristics and high-performance object detection provides increased productivity

High immunity to optical interference reduces false readings

Rugged metal housing (optional Teflon® coating available) requires less maintenance due to its resistance to high-pressure cleaning environments

Quick and easy threshold adjustment (depending on type)

Simple monitoring of detection quality

Key lock function and parameter download prevent incorrect setting



Cechy

Zasada działania czujnika/Sposób detekcji:	Fotoprzełącznik refleksyjny, autocollimation
Wymiary (Szer. x Wys. x Głęb.):	15,6 mm x 48,5 mm x 42 mm
Housing design (light emission):	Prostopadłościenna
Maks. strefa działania:	0 m ... 4 m ¹⁾
Rodzaj światła:	Widzialne światło czerwone
Nadajnik światła:	LED ²⁾
Długość fali:	640 nm
Kąt promieniowania:	Ca. 1,5 °
Nastawa:	Potencjometr, 5 obrotów
Średnica plamki świetlnej (odległość):	Ø 100 mm (3 m)

Continuous threshold adaption:

-

¹⁾ PL80A ²⁾ Average service life of 100,000 h at $T_A = +25\text{ °C}$


Mechanika/elektronika

Switching output:	PNP
Tryb przełączania:	Przełączanie jasno/ciemno, wybierane
Output current I _{max} :	100 mA
Czas reakcji:	$\leq 330\text{ }\mu\text{s}$ ¹⁾
Switching frequency:	$\pm 1.500\text{ Hz}$ ²⁾
Sposób przyłączenia:	Connector M12, 4-pin
Układ zabezpieczenia::	A, C, D ³⁾ ⁴⁾ ⁵⁾
Klasa ochrony:	II
Ciężar:	120 g
Filtr polaryzacyjny:	✓
Special device:	✓
Tworzywo, obudowa:	Metal
Rodzaj zabezpieczenia:	IP 66 IP 67 IP 69K
Emitancja:	Do obiektów transparentnych
Funkcje specjalne:	Pin assignment: 1 = L+ / 3 = 0 V / 4 = Q / 2 = NC
Ambient operating temperature:	-40 °C ... 60 °C
Ambient storage temperature:	-40 °C ... 75 °C
UL File No.:	NRKH.E181493 & NRKH7.E181493

¹⁾ Signal transit time with resistive load ²⁾ With light/dark ratio 1:1 ³⁾ A = V_S connections reverse-polarity protected ⁴⁾ C = interference suppression ⁵⁾ D = outputs


overcurrent and short-circuit protected

Dimensional drawing




- |1| Optical axis
- |2| LED indicator yellow: Light received
- |3| Green LED indicator: supply voltage active
- |4| M4 threaded mounting hole, 4 mm deep
- |5| Mounting hole, Ø 4.2 mm
- |6| Sensitivity adjustment: poti
- |7| Connection

Adjustments possible




- |2| LED indicator yellow: Light received
- |3| LED indicator, green: power on, teach-in mode I, LED indicator, blue: teach-in mode II
- |6| Single teach button, function 1: teach-in sensitivity on reflector, function 2: change operation/teach-in mode

Connection diagram




Sensing range diagram




■ Sensing range max.

Connection type



Light spot size



Australia

Phone +61 3 9457 0600
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Česká republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail info@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6801000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederland

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail sales.gsg@sick.com

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886-2-2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com