



Fotoprzełączniki W12-2 Laser, Fotoprzełącznik refleksyjny, autocollimation

WL12L-2P130



Nazwa modelu > **WL12L-2P130**

Numer części > **1022041**



Produkt może różnić się od ilustracji

At a glance

- Laser protection class 1 or 2
- Autocollimation optics
- Rugged sensors for industrial use
- Highly visible laser light spot for versatile detection of objects
- Rugged die-cast zinc housing with optional Teflon® coating
- Versatile mounting options due to dovetail mounting - mounting holes and oblong holes
- Highly visible status LEDs
- Adjustable sensing range and focus

Your benefits

Reliable detection of all types of objects

High immunity to optical interference ensures fewer false readings and less downtime

Highly visible laser light spot provides quick and easy setup

Highly visible status LEDs simplify commissioning and reduce installation time

Rugged metal housing (optional Teflon® coating available) requires less maintenance due to its resistance to high-pressure cleaning environments

Laser protection class 1 or 2 for eye safety

Rotatable connectors simplify installation



Cechy

Zasada działania czujnika/Sposób detekcji:	Fotoprzełącznik refleksyjny, autocollimation
Wymiary (Szer. x Wys. x Głęb.):	15 mm x 49 mm x 41,5 mm
Housing design (light emission):	Prostopadłościenna
Maks. strefa działania:	0 m ... 18 m ¹⁾
Rodzaj światła:	Widzialne światło czerwone
Nadajnik światła:	Laser ²⁾
Light spot (distance):	0,8 mm (300 mm)
Długość fali:	650 nm
Nastawienie czułości:	Potentiometer


¹⁾ PL80A ²⁾ Average service life 50,000 h at Ta = +25 °C

Mechanika/elektronika

Napięcie zasilania:	10 V DC ... 30 V DC ¹⁾
Tętnienia resztkowe:	$\leq 5 V_{SS}$ ²⁾
Current consumption:	$\leq 55 \text{ mA}$ ³⁾
Wyjście przełączające:	NPN, Dark-switching, 0 V oder unbeschaltet, hellschaltend, PNP, Light-switching, Selectable via L/D control wire, Uv, dark-switching
Napięcie sygnału PNP HIGH/LOW:	$U_v - < 2,9 \text{ V}$, $U_v V/0 \text{ V} \leq 1,5 \text{ V}$
Napięcie sygnału NPN HIGH/LOW:	$U_v - < 2,9 \text{ V}$, $U_v V/0 \text{ V} \leq 1,5 \text{ V}$
Output current I _{max} :	100 mA
Czas reakcji:	$\leq 200 \mu\text{s}$ ⁴⁾
Switching frequency:	2.500 Hz ⁵⁾
Sposób przyłączenia:	Cable, 4-wire, 2 m
Układ zabezpieczenia:::	A, C, D ⁶⁾ ⁷⁾ ⁸⁾
Klasa ochronności:	II
Filtr polaryzacyjny:	✓
Rodzaj zabezpieczenia:	IP 67 IP 69K
Ambient operating temperature:	-10 °C ... 50 °C
Ambient storage temperature:	-25 °C ... 75 °C
UL File-No.:	UL No. NRKH.E181493, CDRH-Konform (0312012-00)


¹⁾ Limit values ²⁾ May not exceed or fall short of V_{SS} ³⁾ Without load ⁴⁾ Signal transit time with resistive load ⁵⁾ With light/dark ratio 1:1 ⁶⁾ A = V_S connections reverse-polarity protected ⁷⁾ C = interference suppression ⁸⁾ D = outputs overcurrent and short-circuit protected

Dimensional drawing




- [1] Operating indicator, green
- [2] LED reception indicator, yellow
- [3] Center of optical axis
- [5] Mounting hole, $\varnothing 4.2 \text{ mm}$
- [6] Focal adjustment
- [7] Sensitivity adjustment

Adjustments possible




- [1] Operating indicator, green
- [2] LED reception indicator, yellow
- [6] Focal adjustment
- [7] Sensitivity adjustment

Characteristic curve




Sensing range diagram



Reflektor-Typ

- ① PL80A
- ② PL50A
- ③ PL40A
- ④ P250
- ⑤ PL30A
- ⑥ PL20A
- ⑦ Reflektionsfolie
Diamond Grade

Connection type



Australia

Phone +61 3 9457 0600
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Ceská Republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail kundenservice@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6801000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederlands

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail admin@sicksgp.com.sg

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886-2-2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com