



Fotoprzełączniki W27-3 Ex, Fotoprzełącznik refleksyjny

WL27X-3P3431



Nazwa modelu > **WL27X-3P3431**

Numer części > **1029955**



Produkt może różnić się od ilustracji

At a glance

- Classification: EX II 3G EX nA op is IIB T4 Gc X, EX II 3D EX tc IIIB T135°C Dc IP67 X according to Directive 94/9/EC (ATEX)
- Corresponds to category 3D/3G
- Conform to standards and ready-to-install: Sensor and additional protective housing (stainless steel 1.4301)
- Long sensing range with a high operating reserve
- Red light for easy alignment
- Reliable operation in industrial environments, even when devices are mounted opposite one another

Your benefits

- Ready-to-install sensors conform to the 3G/3D category for explosive zones (ATEX)
- Less contamination due to high operating reserves, reducing downtime
- Resistant to vibrations, reducing downtime
- Withstands harsh environments, making it suitable for a wide range of applications with operating temperatures from -20 °C - +50 °C



Cechy

Zasada działania czujnika/Sposób detekcji:	Fotoprzełącznik refleksyjny
Wymiary (Szer. x Wys. x Głęb.):	31,4 mm x 112,3 mm x 70,4 mm
Housing design (light emission):	Prostopadłościenna
Maks. strefa działania:	0,1 m ... 15 m ¹⁾
Sensing range:	0,1 m ... 11 m ²⁾
Rodzaj światła:	Widzialne światło czerwone
Nadajnik światła:	LED ³⁾
Długość fali:	660 nm
Kąt promieniowania:	Ca. 1,5 °
Nastawa:	Potentiometer
Średnica plamki świetlnej (odległość):	Ø 220 mm (10 m)

^{1) 2)} PL80A ³⁾ Average service life of 100,000 h at T_A = +25 °C


Mechanika/elektronika

Napięcie zasilania:	10 V DC ... 30 V DC ¹⁾
Tętnienia resztkowe:	≤ 5 Vss ²⁾
Pobór prądu:	≤ 35 mA ³⁾


Switching output:	PNP
Tryb przełączania:	Komplementarne
Tryb przełączania:	Przełączanie jasno/ciemno, wybierane
Output current I _{max} :	≤ 100 mA
Czas reakcji:	≤ 500 μs ⁴⁾
Switching frequency:	1.000 Hz ⁵⁾
Typ połączenia:	Cable with connector M12, 4-pin
Układ zabezpieczenia:::	A, B, C ⁶⁾ 7) 8)
Klasa ochronności:	II ⁹⁾
Ciężar:	750 g
Filtr polaryzacyjny:	✓
Tworzywo, obudowa:	ABS, Stainless steel, Stainless steel V2A (1.4301), Tworzywo sztuczne
Tworzywo, układ optyczny:	PMMA
Rodzaj zabezpieczenia:	IP 67
Oznakowanie strefy zagrożonej (ATEX):	EX II 3G EX nA op is IIB T4 Gc X
Kategoria strefy zagrożonej:	3D, 3G
Ambient operating temperature:	-20 °C ... 50 °C
Ambient storage temperature:	-40 °C ... 75 °C
Napięcie sygnału PNP HIGH/LOW:	Approx. VS - 2.5 V / 0 V

¹⁾ Limit values, operation in short-circuit protected network max. 8 A ²⁾ May not exceed or fall short of V_S tolerances ³⁾ Bez obciążenia ⁴⁾ Signal transit time with resistive load
⁵⁾ With light/dark ratio 1:1 ⁶⁾ A = V_S connections reverse-polarity protected ⁷⁾ B = inputs and output reverse-polarity protected ⁸⁾ C = interference suppression
⁹⁾ Reference voltage: 50 V DC

Dimensional drawing




Adjustments possible




[6] Sensitivity adjustment: poti

Connection diagram




Characteristic curve



- |1| PL80A
- |3| PL40A
- |5| PL20A
- |7| Reflective tape Diamond Grade

Sensing range diagram




- |1| PL80A
- |2| PL50A
- |3| PL40A
- |4| PL30A
- |5| PL20A
- |6| C110A
- |7| Reflective tape Diamond Grade

Reflector type

- ① PL80A
- ② PL50A
- ③ PL40A
- ④ PL30A
- ⑤ PL20A
- ⑥ C110
- ⑦ Reflective tape Diamond Grade

Connection type



Australia

Phone +61 3 9457 0600
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Ceská Republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail kundenservice@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6801000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederlands

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail admin@sicksgp.com.sg

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886-2-2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com