




Fotoprzekaźniki W9-3 Glass, Fotoprzekaźnik refleksyjny, autocollimation

WL9G-3P1132



Nazwa modelu > **WL9G-3P1132**

Numer części > **1049081**



Produkt może różnić się od ilustracji

At a glance

- High-performance clear material retro-reflective sensor in ultra-rugged VISTAL™ housing
- Best-in-class optical performance for transparent object detection
- Continuous threshold adjustment
- PinPoint LED for highly visible and precise light spot
- Variable mounting with M3 hole pattern
- Wide range of connection options

Your benefits

- Rugged VISTAL™ housing provides reliable installation and operation
- Best-in-class optical performance for transparent object detection
- Quick and easy alignment due to the highly visible PinPoint light spot
- M3 slotted hole mounting for multiple mounting possibilities
- One housing with a wide variety of options makes machine integration easy
- Variety of accessories for simple mounting



Cechy

Zasada działania czujnika/Sposób detekcji:	Fotoprzełącznik refleksyjny, autocollimation
Wymiary (Szer. x Wys. x Głęb.):	12,2 mm x 50 mm x 23,6 mm
Housing design (light emission):	Prostopadłościenna
Mounting hole:	M3
Maks. strefa działania:	0 m ... 5 m ¹⁾
Sensing range:	0 m ... 3 m ²⁾
Rodzaj światła:	Widzialne światło czerwone
Nadajnik światła:	Pin Point LED ³⁾
Długość fali:	650 nm
Teach-in:	Single teach-in button
Nastawa:	Teach-in
Średnica plamki świetlnej (odległość):	Ø 45 mm (1,5 m)
Continuous threshold adaption:	✓

^{1) 2)} PL80A ³⁾ Average service life of 100,000 h at T_A = +25 °C


Mechanika/elektronika

Napięcie zasilania:	10 V DC ... 30 V DC ¹⁾
Tętnienia resztkowe:	< 5 Vss ²⁾


Current consumption:	$\leq 20 \text{ mA}$ ³⁾
Wyjście przełączające:	PNP ⁴⁾
Tryb przełączania:	Komplementarne
Tryb przełączania:	Przełączanie jasno/ciemno, wybierane ⁵⁾
Output current I _{max} :	$\leq 100 \text{ mA}$ ⁶⁾
Czas reakcji:	$< 0,5 \text{ ms}$ ⁷⁾
Switching frequency:	1.000 Hz ⁸⁾
Sposób przyłączenia:	Cable, 4-wire, 2 m ⁹⁾
Cable material:	PVC
Przekrój przewodu:	0,14 mm ²
Układ zabezpieczenia:::	A, B, C ¹⁰⁾ ¹¹⁾ ¹²⁾
Klasa ochronności:	III
Ciężar:	80 g
Filtr polaryzacyjny:	✓
Tworzywo, obudowa:	Tworzywo sztuczne, VISTAL
Tworzywo, układ optyczny:	PMMA
Rodzaj zabezpieczenia:	IP 66 IP 67 IP 69K
Emitancja:	Do obiektów transparentnych
Ambient temperature operation:	-40 °C ... +60 °C
Ambient storage temperature:	-40 °C ... +75 °C
UL File No.:	NRKH.E181493

¹⁾ Limit values, operation in short-circuit protected network max. 8 A ²⁾ May not exceed or fall short of V_S tolerances ³⁾ Bez obciążenia ⁴⁾ ⁵⁾ Q = light-switching ⁶⁾ As
of Tu 50 °C, a max. load current I_{max} = 50 mA is permitted ⁷⁾ Signal transit time with resistive load ⁸⁾ With light/dark ratio 1:1 ⁹⁾ Do not bend below 0 °C ¹⁰⁾ A = V_S
connections reverse-polarity protected ¹¹⁾ B = inputs and output reverse-polarity protected ¹²⁾ C = interference suppression


Dimensional drawing




Adjustments possible




Connection diagram




Characteristic curve




Sensing range diagram



Connection type



Light spot size



Australia

Phone +61 3 9457 0600
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Česká republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail info@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6801000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederland

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail sales.gsg@sick.com

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886-2-2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com