



Fotoprzełączniki W45, Fotoprzełącznik barierowy

WS/WE45-R260



SICK
Sensor Intelligence.

Nazwa modelu > **WS/WE45-R260**

Numer części > **1010995**



Produkt może różnić się od ilustracji

At a glance

- Long sensing range
- Rugged metal housing
- Optional: Powerful front lens heating
- Optional test input, time delays and alarm output
- Variants for 10 - 60 V DC or 24 - 240 V DC / 24 - 240 V AC voltage supply

Your benefits

- Very long sensing range with a high operating reserve at 100 m provides reliable continuous operation
- Rugged metal housing ensures a long service life in harsh industrial environments
- Front lens heating prevents condensation and frost for reliable operation in outdoor applications
- Scope alignment aid ensures easier alignment to long sensing ranges
- Multiple functions for simpler integration of individual systems
- Variants DC voltage and universal AC/DC voltage provides installation flexibility due to same housing



Cechy

Zasada działania czujnika/Sposób detekcji:	Fotoprzełącznik barierowy
Wymiary (Szer. x Wys. x Głęb.):	60 mm x 105 mm x 105 mm
Housing design (light emission):	Prostopadłościenna
Maks. strefa działania:	0 m ... 350 m
Sensing range:	0 m ... 300 m
Rodzaj światła:	Światło podczerwone
Nadajnik światła:	LED ¹⁾
Typ czasu:	Time delay off, ON and OFF delay, Przełącznik z opóźniaczem
Czas opóźnienia:	Adjustable via time delay selector switch: 0,5 ... 12 s
Kąt promieniowania:	Ca. 0,9 °
Nastawa:	Potentiometer
Średnica plamki świetlnej (odległość):	Ø 4,5 m (300 m)

¹⁾ Average service life of 100,000 h at T_A = +25 °C


Mechanika/elektronika

Napięcie zasilania:	24 V AC/DC ... 240 V AC/DC ¹⁾
Pobór mocy, nadajnik:	≤ 3 VA


Pobór mocy, odbiornik:	≤ 3 VA
Wyjście przełączające:	Relay
Tryb przełączania:	Change-over contacts
Tryb przełączania:	Przełączanie jasno/ciemno, wybierane ²⁾
Output characteristic:	Electrically isolated
Switching mode selector:	Light-/dark-switching selectable via time delay selector switch
Maks. prąd łączeniowy:	4 A (24 V DC), 4 A (240 V AC)
Czas reakcji:	≤ 10 ms
Switching frequency:	10 Hz ³⁾
Sposób przyłączenia:	Terminal connection with PG13,5, 6-pin
Układ zabezpieczenia:	A, C ⁴⁾ ⁵⁾
Klasa ochronności:	I
Ciężar:	1.600 g
Ogrzewanie przedniej szyby:	-
Special device:	-
Tworzywo, obudowa:	Metal
Rodzaj zabezpieczenia:	IP 67
Funkcje specjalne:	Pulsating
Usage category:	AC-15, DC-13, According to EN 60947-1
Ambient operating temperature:	-25 °C ... 55 °C ⁶⁾
Ambient storage temperature:	-40 °C ... 70 °C
UL File No.:	NRKH.E181493 & NRKH7.E181493

¹⁾ +10 %, -25% ²⁾ Provide suitable spark suppression for inductive or capacitive loads ³⁾ With light/dark ratio 1:1 ⁴⁾ A = V_S connections reverse-polarity protected ⁵⁾ C
 = interference suppression ⁶⁾ Up to 140 °C with cooling plates (see accessories)


Dimensional drawing




Adjustments possible




Connection diagram




Characteristic curve



Sensing range diagram



Connection type



Australia

Phone +61 3 9457 0600
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Ceská Republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail kundenservice@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6801000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederlands

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail admin@sicksgp.com.sg

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886-2-2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com