



## Fotoprzełączniki W4S-3 Inox, Fotoprzełącznik odbiciowy, Tłumienie tła

WTB4S-3P3232V



Nazwa modelu > **WTB4S-3P3232V**

Numer części > **1046398**



*Produkt może różnić się od ilustracji*

#### At a glance

- WashDown rated for fluid tightness (IP 66, IP 67, IP 68 and IP 69K) and Ecolab certified
- Tough stainless steel housing (316L/1.4404)
- Resistant to a variety of common cleaning and disinfection agents
- Modern electrical connection available - M12 connector with pin casting
- Best background and extraneous light suppression in its class with OES3 technology and two emitter LED's
- Flexible sensing ranges and hysteresis settings
- Key lock function, remote teach, quality monitoring

#### Your benefits

- Long service life in harsh conditions ensures less downtime and fewer replacement costs
- OES3 technology and special optical design ensures reliable detection of objects at an extended range which ensures less machine downtime caused by faulty switching
- Quick and easy alignment due to highly visible PinPoint emitter LED
- Easy adjustment via a stainless steel metal membrane teach-in pushbutton
- Quick and easy format adjustment
- Easy monitoring of sensor status
- Key lock function and parameter download prevent incorrect settings
- Simple sensor cloning



#### Cechy

|                                            |                                          |
|--------------------------------------------|------------------------------------------|
| Zasada działania czujnika/Sposób detekcji: | Fotoprzełącznik odbiciowy, Tłumienie tła |
| Wymiary (Szer. x Wys. x Głęb.):            | 15,25 mm x 49,2 mm x 22,2 mm             |
| Housing design:                            | Washdown                                 |
| Housing design (light emission):           | Prostopadłościenna                       |
| Maks. strefa działania:                    | 4 mm ... 120 mm <sup>1)</sup>            |
| Sensing range:                             | 10 mm ... 120 mm <sup>2)</sup>           |
| Rodzaj światła:                            | Widzialne światło czerwone               |
| Nadajnik światła:                          | Pin Point LED <sup>3)</sup>              |
| Długość fali:                              | 650 nm                                   |
| Teach-in:                                  | Single teach-in button                   |
| Nastawa:                                   | Teach-in                                 |
| Średnica plamki świetlnej (odległość):     | Ø 2,5 mm (50 mm)                         |


1) 2) Obiekt odbijający 90% światła (standardowy biały zgodnie z normą DIN 5033) 3) Average service life of 100,000 h at T<sub>A</sub> = +25 °C

## Mechanika/elektronika


|                                   |                                                      |
|-----------------------------------|------------------------------------------------------|
| Napięcie zasilania:               | 10 V DC ... 30 V DC <sup>1)</sup>                    |
| Current consumption:              | ≤ 30 mA <sup>2)</sup>                                |
| Wyjście przełączające:            | PNP                                                  |
| Tryb przełączania:                | Komplementarne                                       |
| Tryb przełączania:                | Przełączanie jasno/ciemno, wybierane                 |
| Output current I <sub>max</sub> : | ≤ 100 mA                                             |
| Czas reakcji:                     | < 0,5 ms <sup>3)</sup>                               |
| Switching frequency:              | 1.000 Hz <sup>4)</sup>                               |
| Sposób przyłączenia:              | Cable with connector M8, 4-pin, 150 mm <sup>5)</sup> |
| Cable material:                   | PVC                                                  |
| Układ zabezpieczenia:::           | A, B, C <sup>6)</sup> 7) 8)                          |
| Klasa ochronności:                | III                                                  |
| Ciężar:                           | 50 g                                                 |
| Special device:                   | -                                                    |
| Tworzywo, obudowa:                | Stainless steel, Stainless steel 316L                |
| Rodzaj zabezpieczenia:            | IP 66<br>IP 67<br>IP 68<br>IP 69K                    |
| Ambient operating temperature:    | -30 °C ... 60 °C, -30 °C ... 70 °C <sup>9)</sup>     |
| Ambient storage temperature:      | -30 °C ... 75 °C                                     |
| UL File No.:                      | NRKH.E181493 & NRKH7.E181493                         |

1) Limit values, reverse-polarity protected, operation in short-circuit protected network: max. 8 A <sup>2)</sup> Bez obciążenia <sup>3)</sup> Signal transit time with resistive load <sup>4)</sup> With light/dark ratio 1:1 <sup>5)</sup> Do not bend below 0 °C <sup>6)</sup> A = V<sub>S</sub> connections reverse-polarity protected <sup>7)</sup> B = inputs and output reverse-polarity protected <sup>8)</sup> C = interference suppression <sup>9)</sup> At UV ≤ 24 V and I<sub>A</sub> < 30 mA


Dimensional drawing




Connection diagram




Characteristic curve



Connection type



Sensing range diagram



- ① Sensing distance on black, 6 % remission
- ② Sensing distance on grey, 18 % remission
- ③ Sensing distance on white, 90 % remission

**Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Česká republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail info@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederland**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail sales.gsg@sick.com

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)