



SIMATIC S7-1500, CM PTP RS232 BA COMMUNICATION MODULE FOR SERIAL CONNECTION RS232, FREEPORT, 3964(R), USS, 19200 KBIT/S, 9-PIN SUB-D CONNECTOR

General information	
Product function	
• I&M data	Yes; I&M 0
Engineering with	
• STEP 7 TIA Portal can be configured/integrated as of version	V12 / V12
• STEP 7 can be configured/integrated as of version	V5.5 SP2 with GSD file
• PROFIBUS as of GSD version/GSD revision	- / -
• PROFINET as of GSD version/GSD revision	V2.3
Installation type/mounting	
Type of fitting, rail mounting	Yes; S7-1500 mounting rail
Input current	
Current consumption (rated value)	35 mA; From the backplane bus
Power	
Power available from the backplane bus	0.65 W

Power losses	
Power loss, typ.	0.6 W
Address area	
Occupied address area	
• Inputs	8 byte
Interfaces	
1st interface	
Interface types	
— RS 232	Yes
Interface types	
RS 232	
• Transmission rate, max.	19.2 kbit/s
• Cable length, max.	15 m
• RS-232 accompanying signals	RTS, CTS, DTR, DSR, RI, DCD
Protocols	
Integrated protocols	
Freeport	
— Telegram length, max.	1 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit
— Parity	None, even, odd, always 1, always 0, any
3964 (R)	
— Telegram length, max.	1 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit
— Parity	None, even, odd, always 1, always 0, any
Frame buffer	
• Buffer memory for message frames	2 kbyte
• Number of message frames which can be buffered	255
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes
• Hardware interrupt	No
Diagnostic messages	
• Diagnostics	Yes
• Wire break	Yes

Diagnostics indication LED	
• RUN LED	Yes; Green LED
• ERROR LED	Yes; Red LED
• Receive RxD	Yes; yellow LED
• Send TxD	Yes; yellow LED
Galvanic isolation	
between the backplane bus and interface	Yes
Isolation	
Isolation checked with	707 V DC (type test)
Ambient conditions	
Operating temperature	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	40 °C
Decentralized operation	
to SIMATIC S7-300	Yes
to SIMATIC S7-400	Yes
to SIMATIC S7-1500	Yes
To standard PROFINET controller	Yes
Supports fast startup	Yes
Dimensions	
Width	35 mm
Height	147 mm
Depth	127 mm
Weights	
Weight, approx.	0.22 kg
last modified:	25.09.2014