



## Fotoprzełączniki G10, Fotoprzełącznik odbiciowy, energetyczny

GTE10-N1212



Nazwa modelu > **GTE10-N1212**

Numer części > **1065869**



Produkt może różnić się od ilustracji

#### At a glance

- Long sensing ranges: up to 2,000 mm
- PinPoint LED with bright and precise light spot
- Immunity to ambient light
- 10 V DC ... 30 V DC or 24 V AC/DC ... 240 V AC/DC power supply with PNP/NPN or relay output
- Small housing design
- Rugged sensor housing with metal-reinforced holes for assembly
- Q-Lock assembly system for mounting and aligning the sensor within a few seconds

#### Your benefits

- Long sensing ranges for maximum operating reserves
- Efficient installation: the GTE10 and the Q-Lock assembly system save valuable hours when mounting and commissioning multiple sensors
- Universal DC or AC/DC power supply for even greater application flexibility
- Highly reliable and durable despite optical interference or mechanical loads
- Wide range of accessories simplifies sensor integration: aids for assembly and connectors



#### Cechy

|                                            |                                         |
|--------------------------------------------|-----------------------------------------|
| Zasada działania czujnika/Sposób detekcji: | Fotoprzełącznik odbiciowy, energetyczny |
| Wymiary (Szer. x Wys. x Głęb.):            | 20 mm x 50 mm x 39 mm                   |
| Housing design (light emission):           | Prostopadłościenna                      |
| Maks. strefa działania:                    | 20 mm ... 1.300 mm <sup>1)</sup>        |
| Strefa działania:                          | 40 mm ... 950 mm <sup>2)</sup>          |
| Rodzaj światła:                            | Widzialne światło czerwone              |
| Nadajnik światła:                          | Pin Point LED <sup>3)</sup>             |
| Długość fali:                              | 625 nm                                  |
| Nastawa:                                   | Potentiometer, 270 °                    |
| Średnica plamki świetlnej (odległość):     | Ø 28 mm (1.400 mm)                      |

<sup>1) 2)</sup> Obiekt odbijający 90% światła (standardowy biały zgodnie z normą DIN 5033) <sup>3)</sup> Average service life of 100,000 h at T<sub>A</sub> = +25 °C


#### Mechanika/elektronika

|                      |                                   |
|----------------------|-----------------------------------|
| Napięcie zasilania:  | 10 V DC ... 30 V DC <sup>1)</sup> |
| Tętnienia resztkowe: | ± 5 Vss <sup>2)</sup>             |
| Pobór prądu:         | ≤ 20 mA                           |


|                                     |                                      |
|-------------------------------------|--------------------------------------|
| Wyjście przełączające:              | NPN, open collector                  |
| Tryb przełączania:                  | Przełączanie jasno/ciemno, wybierane |
| Switching mode selector:            | Selectable via light/dark selector   |
| Output current I <sub>max</sub> :   | ≤ 100 mA                             |
| Czas reakcji:                       | ≤ 500 μs <sup>3)</sup>               |
| Sposób przyłączenia:                | Cable, 3-wire, 2 m <sup>4)</sup>     |
| Cable material:                     | PVC                                  |
| Conductor cross-section:            | 0,14 mm <sup>2</sup>                 |
| Układ zabezpieczenia::::            | A, B, C, D <sup>5) 6) 7) 8)</sup>    |
| Klasa ochronności:                  | III                                  |
| Ciężar:                             | 90 g                                 |
| Filtr polaryzacyjny:                | -                                    |
| Rodzaj zabezpieczenia:              | IP 67                                |
| Dostawa:                            | Mounting bracket BEF-G10DC01         |
| Kompatybilność elektromagnetyczna:: | EN 60947-5-2                         |
| Ambient operating temperature:      | -30 °C ... +60 °C                    |
| Ambient storage temperature:        | -40 °C ... +70 °C                    |
| UL File No.:                        | NRKH.E348498 & NRKH7.E348498         |
| Further standards:                  | UL325 <sup>9)</sup>                  |
| Switching frequency max.:           | 1.000 Hz <sup>10)</sup>              |
| Housing material:                   | PVC/PMMA, Tworzywo sztuczne          |

<sup>1)</sup> Limit values; operation in short-circuit protected network max. 8 A    <sup>2)</sup> May not exceed or fall short of V<sub>S</sub> tolerances    <sup>3)</sup> Signal transit time with resistive load    <sup>4)</sup> Do not bend below 0 °C    <sup>5)</sup> A = V<sub>S</sub> connections reverse-polarity protected    <sup>6)</sup> B = inputs and output reverse-polarity protected    <sup>7)</sup> C = interference suppression    <sup>8)</sup> D = outputs overcurrent and short-circuit protected    <sup>9)</sup> Complies with the UL325 standard when used with sturdy protection hood (e.g. BEF-G10WSG, 2071960).    <sup>10)</sup> With light/dark ratio 1:1

## Rysunek techniczny




## Adjustments possible




- [6] Sensing range adjustment
- [7] Light/dark selector

## Connection diagram




## Operating reserve

Operating reserve




- [1] Sensing range on white, 90 % remission
- [2] Sensing range on gray, 18 % remission
- [3] Sensing range on black, 6 % remission

Strefa działania



Średnica plamki świetlnej



**Australia**

Phone +61 3 9457 0600  
1800 33 48 02 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail marketing@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Česká republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail info@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6881000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 5309 2112  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederland**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail sick@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail sales.gsg@sick.com

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886 2 2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 88 65 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 (800) 325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)