



Czujniki widelkowe WFM

WFM180-120P321



Nazwa modelu > **WFM180-120P321**

Numer części > **6037836**



Produkt może różnić się od ilustracji

At a glance

- Highly visible red emitted light
- No setup, out-of-the-box operation
- 360° output indicator
- 5 fork sizes: maximum depth 120 mm, maximum width 180 mm
- Rugged, IP 67 aluminum housing

Your benefits

- Fixed housings guarantee a high level of operational safety with simple commissioning
- A visible red light enables easy alignment and fast adjustment
- The 360-degree yellow output indicator makes continual process control possible
- A wide range of different fork sizes increases installation flexibility
- The aluminum housing meets all requirements for use in harsh industrial conditions



Cechy

Sposób działania:	Optical detection principle
Fork width:	180 mm
Fork depth:	124 mm
Label detection:	-
Nadajnik światła:	LED
Rodzaj światła:	Widzialne światło czerwone
Nastawa:	None
Tryb przełączania:	Dark switching
Housing design (light emission):	Fork shaped
Minimum detectable object (MDO):	1 mm

Mechanika/elektronika

Tętnienia resztkowe ¹⁾ :	< 10 %
Pobór prądu ²⁾ :	< 20 mA
Switching frequency ³⁾ :	4 kHz
Czas reakcji ⁴⁾ :	125 µs
Stability of response time:	± 15 µs
Wyjście przełączające:	NPN: HIGH = approx. VS/LOW ≤ 1.5 V PNP: HIGH = VS - ≤ 1.5 V/LOW = 0 V
Tryb przełączania:	PNP
Output current I _{max} :	100 mA

Initialization time:

Sposób przyłączenia:

Klasa ochronności⁵⁾:

Układ zabezpieczenia:

Rodzaj zabezpieczenia:

Ciężar:

Housing material:

Napięcie zasilania:

Bezpieczna jasność otoczenia:

Fieldbus interface:

140 ms

Connector M8, 3-pin

III

Vs connections reverse-polarity protected
Wyjście Q zabezpieczone przed zwarciami
Tłumienie interferencji

IP 67

Ca. 80 g ... 190 g⁶⁾

Aluminium, Metal

10 V DC ... 30 V DC⁷⁾

Sunlight: ≤ 10.000 klx

-

1) May not exceed or fall short of V_S tolerances

2) Bez obciążenia

3) With light/dark ratio 1:1

4) Signal transit time with resistive load

5) Reference voltage DC 50 V

6)

7) Limit values, reverse-polarity protected, operation in short-circuit protected network: max. 8 A

Dane otoczenia

Obciążenie uderzeniowe:

UL File No.:

Ambient operating temperature:

Ambient storage temperature:

According to EN 60068-2-27


NRKH.E191603 & NRKH7.E191603

-10 °C ... +60 °C¹⁾

-40 °C ... +80 °C

1) Do not bend below 0 °C

Rysunek techniczny



Dimensions in mm (inch)


	A	B	C	C1
	Fork width	Fork depth		
WFM30	30 (1.18)	42 (1.65)	30 (1.18)	6.5 (0.26)
WFM50	50 (1.97)	60 (2.36)	40 (1.57)	6.5 (0.26)
WFM80	80 (3.15)	60 (2.36)	70 (2.76)	6.5 (0.26)
WFM120	120 (4.72)	124.3 (4.89)	100 (3.94)	17 (0.67)
WFM180	180 (7.09)	124.3 (4.89)	152 (5.98)	22 (0.87)

	C2	C3	a	b
WFM30	- (-)	- (-)	54 (2.13)	67.7 (2.67)
WFM50	8 (0.31)	19.5 (0.77)	74 (2.91)	85.7 (3.37)
WFM80	8 (0.31)	19.5 (0.77)	104 (4.09)	85.7 (3.37)
WFM120	10 (0.39)	17 (0.67)	144 (5.67)	150.2 (5.91)
WFM180	8 (0.31)	22 (0.87)	204 (8.03)	150.2 (5.91)

- |1| Optical axis
- |2| Mounting hole, Ø 4.3 mm
- |3| WFM50/80/120/180
- |4| Transmitted light (red)
- |5| Function signal indicator (yellow), switching output

Image Unavailable
f:\Saqqara\im0057233.jpg

Connection diagram



Australia

Phone +61 3 9457 0600
1800 33 48 02 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail marketing@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Česká republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail info@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6881000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 5309 2112
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederland

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail sick@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail sales.gsg@sick.com

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886 2 2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 88 65 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 (800) 325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com